

609

B9906050

FOR REFERENCE

not to be taken from this room

609

TAT10.3
H3
H64
No. 609

REPORT

to

GENTRY, HAWAII, LTD.

Honolulu, Hawaii

on

SOILS INVESTIGATION

for

HEEIA LANDING AREA 6 STOCKPILE

Heeia, Oahu, Hawaii

TMK: 4-6-16: 1

by

GJ. HAWAII, LTD.

807 Ilaniwai Street

Honolulu, Hawaii 96813

SEPTEMBER, 1973

MUNICIPAL REFERENCE & RECORDS CENTER
City & County of Honolulu
City Hall Annex 658 S. King Street
Honolulu, Hawaii 96813

WITHDRAWN



GJ HAWAII, LTD.

807 ILANIWAI STREET • MONOLULU, HAWAII 96813 • PHONE (808) 523-1661

Consultants in the Applied Earth Sciences

File No. R3-0039-H1
27 September 1973

Gentry Hawaii, Ltd.
146 Hekili Street
Kailua, Oahu, Hawaii 96734

Attention: Mr. Harvey Gerwig

Subject: Heeia Landing Area 6 Stockpile
Heeia, Oahu, Hawaii
SOILS INVESTIGATION


Gentlemen:

Transmitted herein are the results of the Soils Investigation accomplished for the Heeia Landing Area 6 Stockpile project. This report was accomplished in accordance with a request from Mr. Harvey Gerwig.

Area 6 Stockpile lies in the Northwest portion of the Heeia Landing project, and is bounded at one extreme by Kamehameha Highway (see Figure 1, Site Plan and Location of Test Borings).

This report was prepared utilizing information obtained from three previous Soils Investigations. These investigations were (a) a preliminary soils reconnaissance performed by Walter Lum and Associates dated 7 June 1971, (b) a preliminary soils investigation by Gribaldo, Jones-Hawaii, Ltd. dated 15 November 1973, and (c) a soils investigation for the Heeia Landing Sewage Lift Station by Gribaldo, Jones-Hawaii, Ltd. dated 19 July 1973.

Figure 1 - Site Plan and Locations of Test Borings



Copies of appropriate boring logs and laboratory test data are attached in the appendix of this report.

Existing Site Conditions

The portion of the site encompassed by Area 6 Stockpile presently exists as unimproved meadowland that has in part been subjected to grazing. The Northwestern boundary of Area 6 is bounded by a dirt road at an approximate average height of six feet above the meadowland. The meadowland is covered by a fairly dense growth of "California" grass.

Subsurface Soil Conditions

The major portion of Area 6 Stockpile is underlain by less than ten feet of soft clays that are in turn underlain by stiff soils. The upper one to two feet of soils are somewhat stiffer than those immediately below them. The groundwater table was encountered within two feet of the existing ground surface.

DISCUSSION, CONCLUSION AND RECOMMENDATIONS

1. We believe that the proposed Heeia Landing Area 6 Stockpile may be developed to support structures, roads, and appurtenances.
2. The method of development we believe to be appropriate for Heeia Landing Area 6 Stockpile is the generation of a pad of fill over the existing native soils. This pad would be utilized to (a) provide bridging over the native soils, (b) provide a surcharge type load over the native soils, and (c) provide a firm base upon which to construct facilities.
3. The variance in existing surface conditions over Area 6, and height of fill to be placed will result in different compaction requirements over the area.
4. Generally, in Area 6, where the final design grade is less than six feet above the existing ground elevation, both the standing grass and grass root mat should be removed. Where the final design grade is more than six feet above the existing ground elevation, only the standing grass need be removed. Existing subsurface, and surface soil conditions may necessitate modification to the above criteria.
5. Where the fill abuts slope banks, all grass, both standing and root mat, must be removed from the existing banks.
6. The degree of compaction obtained in Area 6 will be dependant upon the in-situ density of the existing surface materials.

The degree of compaction required will be as high as can be attained without causing damage to the underlying subsurface soils. It is anticipated that the amount of compaction possible will increase with increasing lifts of fill.

7. The top four feet of fill should have a relative compaction of 90%. In roadway areas 95% relative compaction for the upper two feet of fill should be attained.

8. We recommend that all construction equipment be as light as possible, and that the use of vibratory equipment be prohibited. With the use of lightweight construction equipment, we anticipate that a working fill pad between one and three feet thick will initially be required across substantial portions of Area 6. The exact thickness of the working pad will be determined by field observations, soil conditions, and the actual construction equipment utilized by the contractor. The compaction requirements specified are not a function of the type of construction equipment utilized. The working pad should be constructed as a wave extending outward from the firm bank.

9. Hauling equipment must utilize designated haul roads and bypasses. Heavily loaded equipment should not be driven onto portions that have been filled. Grading and compaction equipment should not be operated with sudden reverses or stops in Stockpile Area No. 6.

10. Should soft areas or excessive pumping be encountered,

work should immediately stop in these areas until the Soils Engineer has been notified, and recommendations for correcting these areas have been given.

11. Loose stockpile heights should not exceed three feet in Area 6 unless authorized by the Soils Engineer. Further, no materials should be stockpiled adjacent to slopes.

12. Samples of material proposed for fill should be submitted to the Soils Engineer no less than four working days before its intended jobsite use.

13. Following completion of filling operations, settlement markers should be installed, and periodic readings taken to evaluate settlements of the subsurface soils.

LIMITATIONS AND UNIFORMITY OF CONDITIONS

1. The recommendations for this report are based upon the assumption that the soils conditions do not deviate from those disclosed in the borings. If any variations or undesirable conditions are encountered during construction, or if the proposed construction will differ from that planned at the present time, GJ Hawaii, Ltd. should be notified so that supplemental recommendations can be given.
2. This report is issued with the understanding that it is the responsibility of the owner, or of his representative, to ensure that the information and recommendations contained herein are called to the attention of the Architect and Engineers for the project and incorporated into the plans, and that the necessary steps are taken to see that the Contractors and Subcontractors carry out such recommendations in the field.
3. The findings of this report are valid as of the present date. However, changes in the conditions of a property can occur with the passage of time, whether they be due to natural processes or to the works of man, on this or adjacent properties. In addition, changes in applicable or appropriate standards occur, whether they result from legislation or the broadening of knowledge. Accordingly, the findings of this report may be invalidated, wholly or partially, by changes outside of our control. Therefore, this report is subject to review and should not be relied

File No. R3-0039-H1
27 September 1973

upon after a period of one year.

Very truly yours,

GJ HAWAII, LTD.

William M. McMorro

William M. McMorro, P.E.
President



Copies: 2 to William Hee and Associates (Attn: W. Hee)
5 to Gentry Hawaii, Ltd. (Attn: H. Gerwig)

APPENDIX

Logs of Borings by GJH

Logs of Borings by Walter Lum & Assoc.

Logs of Swedish Vane Shear Probes

Consolidation Curves

File No. R3-0039-H1
27 September 1973

DEPTH IN FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
0				▽ Boring No. 1		
				Grass mat		
1-1			2	Dark grey Silty CLAY with organics saturated, soft (OH)* (Torvane = 625 p.s.f.)	80.6	36.5
1-2			15	(Grading to stiff, less Clay) (Torvane = 625 p.s.f.)	64.2	57.4
1-3			19	(Grading to brown color with seams of blue-grey) (Torvane = 1625 p.s.f.) (Direct shear: $\phi=70^\circ$, $c=1630$ psf)	67.6	46.1
1-4			30	Dark grey-brown CLAY with traces of Silt, some mottling, saturated, hard (OH) (Torvane = 1375 p.s.f.)	48.7	80.1
1-5			50	(Grading to grey-black color with shells, very hard) (Torvane = 1500 p.s.f.) (Direct shear: $\phi=37^\circ$, $c=740$ psf)	60.2	47.5
1-6			40	(Grading to hard) (Torvane = 2250 p.s.f.)	60.0	60.5

Figure 2 - Log of Boring No 1

DEPTH IN FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
				Boring No. 1 (continued)		
30.	1-7		35	Dark grey/black CLAY with traces of Silt, saturated, hard (OH) Blue-grey Silty CLAY with organics saturated, very stiff (OL) (Torvane = 2375 p.s.f.)	68.4	43.8
35.	1-8		21	White Silty CLAY with fine coral Sand and seams of blue-grey soft Silty CLAY, organics and shells, saturated, soft (CL) (Torvane = 500 p.s.f.) (Direct shear: $\phi = 31^\circ$, $c = 150$ p.s.f.)	85.0	37.2
40.	1-9		24	(Torvane = 500 p.s.f.) (Unconfined strength = 351 p.s.f.)	82.6	38.0
45.	1-10		42	Grey/white Sandy SILT with a Clay binder and traces of Rock fragments, saturated, hard (ML) (Torvane = 1250 p.s.f.)	85.4	34.5
50.	1-11		80	(Grading to very hard) (Torvane = 1000 p.s.f.) (Direct shear: $\phi = 35^\circ$, $c = 600$ p.s.f.)	83.0	37.8
55.	1-12		120	Light grey Clayey SILT with some fine Sand, saturated, soft (ML) (Torvane = 1125 p.s.f.)	76.5	33.1

Figure 2a - Log of Boring 1 (continued)

DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY p.c.f.	MOISTURE CONTENT % dry wt.
56				Boring No. 1 (continued)		
56 57 58 59 60 61 62 63 64 65				Light grey Clayey SILT, some fine Sand, saturated, soft (ML)		
65	1-13		100 4"	Light grey Sandy SILT with a Clay binder, saturated, very dense (ML) (Torvane = 750 p.s.f.) (Unconfined strength = 1290 p.s.f.)	92.5	31.3
70	1-14		40/2'		88.0	30.7
70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85				Dark grey GRAVEL with Sand and some Silt in a Clay binder, saturated, very dense (GW)		
83	1-15		28	Grey Gravelly CLAY with some Sand and Silt, saturated, medium dense	58.4	65.0
84						

Figure 2b - Log of Boring 1 (continued)

File No. R3-0039-H1
27 September 1973

DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
86				Boring No. 1 (continued)		
88				Grey Gravelly CLAY with some Sand and Silt, saturated, medium dense		
90						
92	1-16		122	Dark green Clayey SILT with Gravel and some Sand, saturated, very hard (Torvane = 375 p.s.f.) (Unconfined strength = 735 p.s.f.)	64.1 (MH)	61.0
94						
96						
98						
100						
102						
104						
106						
108						
110						
112						
114						
116						
118						
120						
122						
124						
126						
128						
130						
132						
134						
136						
138						
140						
142						
144						
146						
148						
150						
152						
154						
156						
158						
160						
162						
164						
166						
168						
170						
172						
174						
176						
178						
180						
182						
184						
186						
188						
190						
192						
194						
196						
198						
200						
202						
204						
206						
208						
210						
212						
214						
216						
218						
220						
222						
224						
226						
228						
230						
232						
234						
236						
238						
240						
242						
244						
246						
248						
250						
252						
254						
256						
258						
260						
262						
264						
266						
268						
270						
272						
274						
276						
278						
280						
282						
284						
286						
288						
290						
292						
294						
296						
298						
300						
302						
304						
306						
308						
310						
312						
314						
316						
318						
320						
322						
324						
326						
328						
330						
332						
334						
336						
338						
340						
342						
344						
346						
348						
350						
352						
354						
356						
358						
360						
362						
364						
366						
368						
370						
372						
374						
376						
378						
380						
382						
384						
386						
388						
390						
392						
394						
396						
398						
400						
402						
404						
406						
408						
410						
412						
414						
416						
418						
420						
422						
424						
426						
428						
430						
432						
434						
436						
438						
440						
442						
444						
446						
448						
450						
452						
454						
456						
458						
460						
462						
464						
466						
468						
470						
472						
474						
476						
478						
480						
482						
484						
486						
488						
490						
492						
494						
496						
498						
500						
502						
504						
506						
508						
510						
512						
514						
516						
518						
520						
522						
524						
526						
528						
530						
532						
534						
536						
538						
540						
542						
544						
546						
548						
550						
552						
554						
556						
558						
560						
562						
564						
566						
568						
570						
572						
574						
576						
578						
580						
582						
584						
586						
588						
590						
592						
594						
596						
598						
600						
602						
604						
606						
608						
610						
612						
614						
616						
618						
620						
622						
624						
626						
628						
630						
632						
634						
636						
638						
640						
642						
644						
646						
648						
650						
652						
654						
656						
658						
660						
662						
664						
666						
668						
670						
672						
674						
676						
678						
680						
682						
684						
686						
688						
690						
692						
694						
696						
698						
700						
702						
704						
706						
708						
710						
712						
714						
716						

File No. R3-0039-H1
27 September 1973

DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
				Boring No. 1 (continued)		
123				Dark green Clayey SILT with Gravel and some Sand, saturated, very hard (MH)		
124						
125						
126						
127						
128						
129						
130				Boring Terminated at 130'		

Figure 2d - Log of Test Boring 1 (continued)

DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY p.c.t.	MOISTURE CONTENT % dry wt.
0				▽ Boring No. 2		
0				≡ Grass mat,		
5			5	Dark grey Silty CLAY with organ- ics, saturated, soft (OH)		
2-1			13	(Torvane = 1125 p.s.f.)	58.9	64.8
10				Dark grey CLAY with some mottled Rocks, saturated, stiff (OH)		
2-2			20	(Grading to blue-green with some Silt, very stiff (Torvane = 1500 p.s.f.)	60.0	69.0
15				(Grading to blue-grey with a trace of Sand and Silt, saturated (Torvane = 1750 p.s.f.) (Direct shear: $\phi = 20^\circ$, $c = 950$ p.s.f.)	58.1	68.3
2-3			22			
20				(Grading to hard, Silt increasing) (Torvane = 2500 p.s.f.)	61.2	63.3
2-4			30			
25				(Torvane=1875 psf)	57.6	62.8
2-5			56	Dark grey Silty CLAY with numer- ous shells and Coral fragments, saturated, very hard (OH)		
28						

Figure 3 - Log of Test Boring 2

File No. R3-0039-H1
27 September 1973


DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
				Boring No. 2 (continued)		
29.0 30.0 31.0 32.0 33.0 34.0 35.0	2-6		64	Dark grey Silty CLAY with numerous shells and Coral fragments, saturated, stiff (OH) (Grading to fewer shells) (Torvane = 1000 p.s.f.)	52.6	74.2
35.0 36.0 37.0 38.0 39.0 40.0 41.0 42.0 43.0 44.0 45.0	2-7		86	Dark grey GRAVEL-CLAY mixture, saturated, dense (GC) (Torvane = 375 p.s.f.)	83.5	34.8
45.0 46.0 47.0 48.0 49.0 50.0 51.0 52.0 53.0 54.0 55.0	2-8		30 48	White Clayey SILT with fine Sand, saturated, hard (MH) (Torvane = 1150 p.s.f.)	83.5	41.2

Figure 3a - Log to Test Boring 2 (continued)

File No. R3-0039-H1
27 September 1973

DEPTH in FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt.
35				Boring No. 2 (continued)		
36				White Clayey, SILT with fine Sand, saturated, hard (MH)		
37						
38						
39						
40						
41						
42						
43			43			
44						
45						
46						
47						
48			48	Sandy CLAY, saturated, very hard		
49						
50						
51						
52						
53						
54						

Figure 3b - Log of Test Boring 2 (continued)

DEPTH IN FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
				Boring No. 2 (continued)		
85				Sandy CLAY, saturated, very hard		
90						
95						
100	2-9	17		Silty CLAY, stiff		
105						
110						
115						
120						
125						
130						
135						
140						
145						
150						
155						
160						
165						
170						
175						
180						
185						
190						
195						
200						
205						
210						
215						
220						
225						
230						
235						
240						
245						
250						
255						
260						
265						
270						
275						
280						
285						
290						
295						
300						
305						
310						
315						
320						
325						
330						
335						
340						
345						
350						
355						
360						
365						
370						
375						
380						
385						
390						
395						
400						
405						
410						
415						
420						
425						
430						
435						
440						
445						
450						
455						
460						
465						
470						
475						
480						
485						
490						
495						
500						
505						
510						
515						
520						
525						
530						
535						
540						
545						
550						
555						
560						
565						
570						
575						
580						
585						
590						
595						
600						
605						
610						
615						
620						
625						
630						
635						
640						
645						
650						
655						
660						
665						
670						
675						
680						
685						
690						
695						
700						
705						
710						
715						
720						
725						
730						
735						
740						
745						
750						
755						
760						
765						
770						
775						
780						
785						
790						
795						
800						
805						
810						
815						
820						
825						
830						
835						
840						
845						
850						
855						
860						
865						
870						
875						
880						
885						
890						
895						
900						
905						
910						
915						
920						
925						
930						
935						
940						
945						
950						
955						
960						
965						
970						
975						
980						
985						
990						
995						
1000						
1005						
1010						
1015						
1020						
1025						
1030						
1035						
1040						
1045						
1050						
1055						
1060						
1065						
1070						
1075						
1080						
1085						
1090						
1095						
1100						
1105						
1110						
1115						
1120						
1125						
1130						
1135						
1140						
1145						
1150						
1155						
1160						
1165						
1170						
1175						
1180						
1185						
1190						
1195						
1200						
1205						
1210						
1215						
1220						
1225						
1230						
1235						
1240						
1245						
1250						
1255						
1260						
1265						
1270						
1275						
1280						
1285						
1290						
1295						
1300						
1305						
1310						
1315						
1320						
1325						
1330						
1335						
1340						
1345						
1350						
1355						
1360						
1365						
1370						
1375						
1380						
1385						
1390						
1395						
1400						
1405						
1410						
1415						
1420						
1425						
1430						
1435						
1440						
1445						
1450						
1455						
1460						
1465						
1470						
1475						
1480						
1485						
1490						
1495						
1500						
1505						
1510						
1515						
1520						
1525						
1530						
1535						
1540						
1545						
1550						
1555						
1560						
1565						
1570						
1575						
1580						
1585						
1590						
1595						
1600						
1605						
1610						
1615						
1620						
1625						
1630						
1635						
1640						
1645					</	






DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
0				Boring No. G6		
0				Reddish brown Clayey SILT with organics, medium stiff, wet		
6-1			4	Mottled rust/grey Silty CLAY, medium stiff, wet (OH)		
5			2	Grey Clayey SAND with fine Gravel and Rocks, loose, wet (SC)		
6-2			2	Grey Silty SAND with shell fragments and coarse Sand, loose, saturated (SM)	69.3	55.7
15			4	(Grading to medium stiff)		
6-3			4	Grey very fine Sandy SILT with slight Clay binder, soft to medium stiff, saturated (ML)		
20			5	(At 20.0', grading to more Clay binder)		
25				Black very fine SAND, loose, saturated (SP)		
28						

Figure No. 7 - Log of Test Boring No. G6

File No. R3-0039-HI
27 September 1973

DEPTH ft.	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf.	MOISTURE CONTENT % dry wt.
28.5				Boring No. G6 (continued)		
29.5						
30.5				Black very fine SAND, loose, saturated (SP)		
31.5	6-5		9		54.1	79.5
32.5						
33.5				Brownish grey Clayey SILT with fine Sand, medium stiff to stiff, saturated (OH)		
34.5						
35.5						
36.5						
37.5						
38.5						
39.5						
40.5	6-6		5	(Grading to medium stiff)	59.2	66.7
41.5						
42.5						
43.5				Break in logs 43' - 53'		
44.5						
45.5						
46.5						
47.5						
48.5						
49.5						
50.5						
51.5						
52.5						
53.5						
54.5						
55.5						
56.5						
57.5						
58.5						
59.5						
60.5						
61.5						
62.5				(At 62.0', grading to very hard)		
63.5	6-7		33/3'			
64.5				Boring Terminated at 63'		
65.5						
66.5						
67.5						
68.5						
69.5						
70.5						
71.5						
72.5						
73.5						
74.5						
75.5						
76.5						
77.5						
78.5						
79.5						
80.5						
81.5						
82.5						
83.5						
84.5						
85.5						
86.5						
87.5						
88.5						
89.5						
90.5						
91.5						
92.5						
93.5						
94.5						
95.5						
96.5						
97.5						
98.5						
99.5						
100.5						

Figure No. 7a - Log of Test Boring No. G6 (continued)

DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf	MOISTURE CONTENT % dry wt
-0-				Boring No. G14		
0				Mottled brown/rust Silty CLAY, medium stiff, wet (OH)		
14-1			5	▽		
3			3	Grey Silty CLAY, soft, saturated (OH)	61.1	62.7
5						
14-2			20	(At 5.0', very stiff)	59.5	70.7
10				Mottled brown/blue Silty CLAY, very stiff, saturated		
14-3			18		55.6	75.1
15						
14-4			21			
			30	Brown Silty CLAY, very stiff, saturated (OH)		
				Coarse black SAND, dense, saturated (SP)		
20				Grey Sandy CLAY, very stiff (SC)		
14-5			25	Bluish grey Silty CLAY, very stiff, saturated (OH)		
25						
23				Grey Silty CLAY with small organic traces, very stiff (OH)		

Figure No. 15 - Log of Test Boring No. G14

File No. R3-0039-H1
27 September 1973


DEPTH FEET	SAMPLE NO.	LOG & LOCATION OF SAMPLE	Penetration Resistance Blows/ft	DESCRIPTION	IN-PLACE	
					DRY DENSITY pcf.	MOISTURE CONTENT % dry wt.
25				Boring G14 (continued)		
30	14-6		30	Grey Silty CLAY with small traces of organics (OH) (At 30.0', traces of Rock fragments)		
35						
38.5			50	GRAVEL-SAND mixture with Rock, very dense		
				Boring Terminated at 38.5'		

Figure No. 15a - Log of Test Boring No. G14 - continued

Boring Log

PROJECT CROWN TERRACE - TRACT 2 UNIT 3
LOCATION Heeia, Koolaupoko, Oahu, Hawaii
HAMMER: 10" SLEDGE HAMMER
Drop: 2" S - 2" O.D. THIN WALL TUBE
SAMPLER: 2" S - 2" STANDARD SPLIT SPOON

BORING NO. 14 Sheet No. of
Driller W. LUM ASSOC., INC. Date MAY 14, 1973
Field Party MAESHIRO, KAKU
Type of Boring AUGER (MOBILE) Diam. 5"
Elev. 110' ± * Datum
Drill Bit T.C. DRAG
Water Level NOT NOTICED
Time
Date 5-14-73

Unified Soil Classification	DESCRIPTION	Depth (Ft.)	Sampler	Sample No.	Wet Dens. P.C.F.	Water Cont. %	Dry Dens. P.C.F.	Unconf. Comp. P.S.F.	Vane Shear P.S.F.	PENETRATION DATA				
										Standard Penetration Test	10" SLEDGE HAMMER			
										N (Blows per foot)	BLOWS			
										0 10 20 30 40				
	ELEV = 110' ± *	0												
(M.F.)	MEDIUM TO STIFF, BROWN, CLAYEY SILT	0	2" S	14-A	100	45	67	3700	1500				51.5'	71.5'
		5	2" S	14-B	98	50	65	11,100					181.5'	201.5'
(M.F.)	STIFF, BROWN & GRAY SILTY CLAY	10	2" S	14-C		50							201.5'	
		15	2" S	14-D		53							201.5'	
		20	2" S	14-E		54							401.5'	
	END OF BORING @ 205'													

* ELEVATION ESTIMATED FROM TOPO MAP

WALTER LUM ASSOCIATES

3030 WAIALAE AVENUE • HONOLULU, HAWAII 96816 • PHONE 777-931


Boring Log

PROJECT NEEIA LOWLANDS
LOCATION Neēia, Koolau-poko, Oahu, Hawaii
Tax Map Key: 4-6-16
HAMMER: 1-0"
Weight: 30"
Drop: 2" 5 - 2" O.D. THIN WALL TUBE
SAMPLER: 2" 55 - 2" STANDARD SPLIT SPOON


BORING NO. 10 Sheet No. of
Driller WALTER LUM ASSOC. Date SEPT. 21, 1973
Field Party MEYER, MAKAULA
Type of Boring AUGER (MOBILE MINUTE MAN) Diam. 3"
Elev. 1' ± * Datum
Drill Bit FINGER TYPE
Water Level 0.4'
Time 11:45 AM
Date 9-21-70

Soil Classification	DESCRIPTION	Depth (ft.)	Sampler	Sample No.	Wet Dens. P.C.F.	Moist. Cont. %	Dry Dens. P.C.F.	Unconf. Comp. P.S.F.	Vane Shear P.S.F.	PENETRATION DATA				
										STANDARD PENETRATION TEST "N"				
										Blows Per Foot				
										0	10	20	30	40
										BLOWS/FT.				
CH-1	SOFT, GRAY & BROWN ORGANIC CLAY	0	2" 55	10-A	-	81	-	-	-					
						LL= 115								
						PL= 44								
CH-2	SOFT, GRAY SILTY SAND W/ SHELLS	5	2" 55	10-B	105	80	58	-	60					
									100					
CH-3	MEDIUM, GRAY & BROWN, CLAYEY SILT (DECOMPOSED ROCK)	10	2" 55	10-C	-	71	-	-	-					
CH-4	MEDIUM, GRAY & BROWN CLAY W/ TRACES OF DECOMPOSED ROCK	15	2" 55	10-D	98	94	52	-	800					
						LL= 155			840					
						PL= 38								
CH-5	MEDIUM TO STIFF, GRAY & BROWN SILTY CLAY (SLIGHTLY ORGANIC)	20	2" 55	10-E	-	81	-	-	-					
						72								
CH-6	STIFF, GRAY ORGANIC SILT, W/ WOOD PIECES	25	2" 55	10-F	-	107	-	-	-					
	END OF BORING @ 26.5'													


V 4



V 5



V 6



DEPTH BELOW EXISTING GROUND SURFACE (Meters)

0 RESISTANCE PRESSURE (Kilograms) 1000

Figure No. 20 - Logs of Swedish Vane Shear Probes No. 4, 5, & 6




Figure No. 23 - Log of Swedish Vane Shear Probe No. 9

CONSOLIDATION CURVE





Figure No. 36 - Consolidation Curve for Sample No. 5-3



CONSOLIDATION CURVE





Figure No. 35 - Consolidation Curves for Samples No. 2-7 & 4-6



CONSOLIDATION CURVE





Figure No. 34 - Consolidation Curves for Samples No. 2-5 & 2-6



CONSOLIDATION CURVE




Figure No. 33 - Consolidation Curves for Samples No. 1-1 & 2-4